

LED Exit Signs

MexLITE Range

The ELP **MexLITE** range of high quality LED exit sign luminaires is perfectly suited to modern architectural environments and available in two sizes for 25m and 30m viewing distances. Offering ease of installation, these luminaires feature a first fix plate. The attractive slim body and legend plate then clips into position. The safety sign legends can be fitted/changed on site by simply clipping the appropriate sign into the frame. (NB: a complete set of EC & ISO legends are supplied with each luminaire).

The framed panel has a specially screen printed finish to ensure uniform illumination of the safety sign legend. Due to their slim design and different mounting options, **MexLITE** luminaires are ideal for integrating into new and existing installations.

The **MexLITE ESA09** and **ESA11** can have the legend panel suspended at different levels by just slipping the wires through the locking clutch bushes. The SELV supply to the LEDs is fed through the suspension wires.

OPERATION

The **MexLITE** luminaires are available with mains only or Maintained emergency operation. (All emergency versions provide 3 hour duration). Maintained versions can be used for standard switched mains lighting but will automatically provide emergency lighting in the event of a complete loss of normal mains supply. (Non-maintained operation is available by excluding a switched live supply).

MexLITE luminaires use the latest high efficiency, white LEDs, a 'smart' energy efficient battery charger/driver circuit and long-life Lithium Iron Phosphate batteries (LiFePO4). The luminaires are designed to fully comply with the relevant parts of EN60598.2.22

DALI/Self-Test Options:

The **MexLITE** LED luminaires can be specified with integral DALI/Self-Test gear providing automatic Self-Test in accordance with BSEN62034 or fully interoperable DALI operation when connected to a DALI control system.

NB: Self-Test is available for all versions *but* DALI operation is only available for the larger sizes — **ESA10 & ESA11**



GENERAL DETAILS

Product	LED Exit Sign (Fixed and Wire Suspended)
Light source	14 x white LEDs
Luminaire Lumens	N/A
Sign viewing distances	25m (ESA08 and ESA09) 30m (ESA10 and ESA11)
Construction	Polycarbonate
Geartray	First fix plate
Dimensions	See line drawings
Cable entry	Top and back (first fix plate)




MXL/ESA08 and MXL/ESA10



Adjustable suspension wire
Length: 15mm to 1metre

MXL/ESA09 and MXL/ESA11



'Universal' First fix plate

All details and specifications shown in this document are deemed correct at time of publication. The right to modify equipment, change specifications and instructions without notice, is reserved as part of the Emergency Lighting Products Limited policy of continuous development and improvement. We endeavour to keep all our customers informed of any alterations as and when they occur.



LED Exit Signs

SPECIFICATION

Light source	14 x white LEDs
Colour temperature	4500K
Luminaire Lumens	N/A
IP Rating	IP40
Ambient temperature (Ta)	25°C
Insulation Class	Class II
Supply voltage	230V ~ 50Hz
Supply power (Maintained)	2.6W (ESA 08/09) 3.1W (ESA 10/11)
Supply power (Non-maintained)	0.8W
Charge power (typical)	0.7W
Battery (LiFePO4)	6.4V 600mAh (standard) 3.2V 3.2Ah (DALI)
Weight	2.5kg (max.)



MXL/ESA09LFP/M3 (small) MXL/ESA11LFP/M3 (large)



Simple height adjustment

Wall/Ceiling Mounting with optional Wire Suspension

MexLITE Exit Signs are suitable for Wall/Ceiling mounting and offer Wire Suspended versions. Mounting is achieved via a first fix plate which has fixing holes suitable for wall or ceiling mounting. The Wire Suspended versions utilise parallel suspension wires that allow the height of the legend to be easily set by the use of two locking clutch bush mechanisms.

Recessed Mounting

MexLITE Exit Signs can be supplied with a ceiling recessing accessory allowing the standard body to recess into a ceiling cut-out mounting bracket. This feature is ideal for applications requiring a more aesthetic installation.



MXL/ESA11LFP/M3/RB (using /RB recessing accessory)


LED Exit Signs

DIMENSIONS

The two styles of MexLITE (fixed and wire suspended) are both available in two different sizes, providing viewing distances of 25 metres and 30 metres.

Large = 30m viewing distance

Small = 25m viewing distance



MXL/ESA11LFP/M3/RB
(with /RB recessing bracket)



MXL/ESA10LFP/M3 (large)
MXL/ESA08LFP/M3 (small)

ORDER CODES

25m viewing distance

- MXL/ESA08LFP/M3
- MXL/ESA08/230
- MXL/ESA09LFP/M3
- MXL/ESA09/230

Description

- Wall/Ceiling Mounted, 3 hour duration, Maintained, Non-Maintained
- Wall/Ceiling Mounted, Mains only
- Wall/Surface Mounted Wire Suspended, 3 hour duration, Maintained, Non-Maintained
- Wall/Surface Mounted Wire Suspended, Mains only
- NB:** All versions supplied with a complete set EC and ISO legend screens

30m viewing distance

- MXL/ESA10LFP/M3
- MXL/ESA10LFP/M3/D
- MXL/ESA10/230
- MXL/ESA11LFP/M3
- MXL/ESA11LFP/M3/D
- MXL/ESA11/230

- Wall/Ceiling Mounted, 3 hour duration, Maintained, Non-Maintained
- Wall/Ceiling Mounted, 3 hour duration, DALI Maintained, Non-Maintained
- Wall/Ceiling Mounted, Mains only
- Surface Mounted Wire Suspended, 3 hour duration, Maintained, Non-Maintained
- Surface Mounted Wire Suspended, 3 hour duration, DALI Maintained, Non-Maintained
- Surface Mounted Wire Suspended, Mains only
- NB:** All versions supplied with a complete set EC and ISO legend screens

OPTIONS:

- /STE Self-Test emergency operation (no DALI operation)
- MXL/ESA08-09/RB Recessing bracket for recessed ceiling applications (For MXL/ESA08 and 09 versions)
- MXL/ESA10-11/RB Recessing bracket for recessed ceiling applications (For MXL/ESA10 and 11 versions)

LEGENDS:

- MXL/ESA08-09/ISO/** MXL/ESA08 or 09 Single ISO format legend panel (**= AR-right; AL-left; AD-down; AU-up)
- MXL/ESA08-09/EC/** MXL/ESA08 or 09 Single EC format legend panel (**= AR-right; AL-left; AD-down; AU-up)
- MXL/ESA10-11/ISO/** MXL/ESA10 or 11 Single ISO format legend panel (**= AR-right; AL-left; AD-down; AU-up)
- MXL/ESA10-11/EC/** MXL/ESA10 or 11 Single EC format legend panel (**= AR-right; AL-left; AD-down; AU-up)

Emergency Lighting Products Limited

Parbrook House, Gillmans Industrial Estate, Natts Lane Billingshurst, West Sussex RH14 9EZ

Telephone: +44 (0) 1403 786601 Fax: +44 (0) 1403 786602 e-mail:sales@elp.uk.com www.elp.uk.com

MEXLITEDS-04-20

