

## IP65 Amenity Luminaires

# Amenity Round

The **Amenity Round** luminaire provides an attractive but robust solution for providing lighting to walkways, tunnels, storage areas, car parks etc.

The enclosure is sealed to IP65 and houses a geartray with HF electronic driver and multi-circuit LED board. The Polycarbonate lens and halo-effect side band provide excellent photometric performance (1250 luminaire lumens).

The robust Cast Aluminium and Polycarbonate enclosure is vandal resistant and provides protection to IP65.

Suitable for ambient temperatures of up to 35°C (25°C for emergency versions) the units are ideal for interior and exterior environments.

### OPERATION

The **Amenity Round** luminaires are available with mains only or Maintained emergency operation. All emergency versions provide 3 hour duration from integral high temperature Nickel Cadmium (NiCd) batteries.

Maintained versions can be used for standard switched mains lighting but will automatically provide emergency lighting in the event of a complete loss of normal mains supply. (Non-maintained operation is available by excluding a switched live supply).

The benefits of the modern white low power LEDs include long life (typically 50,000hours+), excellent energy efficiency (>100lm/W), low operating temperatures therefore improving the life of the internal batteries and good operation at low ambient temperatures.

These luminaires incorporate high quality mains drivers and separate state of art emergency gear. Therefore, combinations of standard (fixed output) or DALI dimming mains drivers with standard or DALI/Self-Test emergency lighting equipment are possible.

The luminaires fully comply to the requirements of EN60598.2.22




### GENERAL DETAILS

Product	Amenity Luminaire
Light source	LED array (2000lm)
Luminaire Lumens	1250lm (Tri-guard 1175lm)
Construction	Cast Aluminium body with Polycarbonate opal lens
Geartray	White PCB fixed by 2 screws
Dimensions	300mm (dia.) x 100mm (H)
Cable entry	20mm holes in back



15605/230



# IP65 Amenity Luminaires

## SPECIFICATION

	Maintained	Mains only
Light source	Surface mounted white LEDs (2000 Lumens)	
Colour temperature	4000K	
Luminaire lumens (mains)	1250lm (Tri-guard 1175lm)	1250lm (Tri-guard 1175lm)
Lumens (emergency)	200lm (Tri-guard 235lm)	N/A
IP rating	IP65	
Ambient temperature (Ta)	25°C	
Insulation class	Class I	
Supply voltage	230V ~ 50Hz	
Supply power	19.2W	16.4W
Charge power (typical)	3.5W	—
Battery	1 x 6.0V 2.0Ah NiCd	—
Weight	3.4kg	2.8kg

## AMENITY ROUND – Emergency Lighting Spacings

Mounting height Hm (m)	Model 15605/M3	
	Spacing (m) min 0.5Lux open area	Spacing (m) min 1Lux escape
2.0	10.7	7.5
2.5	11.3	7.6
3.0	12.3	7.8
4.0	12.5	8.2



15606/230  
Tri-guard

### ORDER CODES

#### Description

<b>15605/M3</b>	Maintained with standard mains driver and standard emergency
<b>15605/M3D</b>	Maintained with standard mains driver and DALI/Self-Test emergency
<b>15605/230D/M3</b>	Maintained with DALI mains and standard emergency
<b>15605/230D/M3D</b>	Maintained with DALI mains and DALI/Self-Test emergency
<b>15605/230</b>	Mains only
<b>15605/230D</b>	Mains only with DALI driver

### Tri-guard versions:

<b>15606/M3</b>	Maintained with standard mains driver and standard emergency
<b>15606/M3D</b>	Maintained with standard mains driver and DALI/Self-Test emergency
<b>15606/230D/M3</b>	Maintained with DALI mains and standard emergency
<b>15606/230D/M3D</b>	Maintained with DALI mains and DALI/Self-Test emergency
<b>15606/230</b>	Mains only
<b>15606/230D</b>	Mains only with DALI driver

**NB:** Contact our Sales Office regarding optional LiFePO4 versions

### Emergency Lighting Products Limited

Parbrook House, Gillmans Industrial Estate, Natts Lane Billingshurst, West Sussex RH14 9EZ

Telephone: +44 (0) 1403 786601 Fax: +44 (0) 1403 786602 e-mail:sales@elp.uk.com [www.elp.uk.com](http://www.elp.uk.com)

LEDAMENITYROUND DS-11-21

