

MetaLED

MetaLED exit sign luminaires feature epoxy coated steel enclosures with screen printed opal polycarbonate legend panels enclosing integral rechargeable batteries and a PCB fitted with advanced wide angle white LEDs and efficient driver circuit. The MetaLED range provides excellent viewing distances of 36 metres.

The luminaire offers bright and even luminance across the legend panel ensuring maximum visibility in the event of an emergency.

OPERATION

The **MetaLED** range is supplied with Maintained operation as standard providing 3 hour duration from integral high temperature Lithium Iron Phosphate (LiFePO₄) batteries. (Non-maintained operation is available by excluding a switched live supply).

DALI/Self-Test Options:

The **MetaLED** LED luminaires can be specified with integral DALI/Self-Test gear providing automatic Self-Test in accordance with BSEN62034 or fully interoperable DALI operation when connected to a DALI control system.

MetaLED luminaires may also be specified with DALI control mains drivers.

NOTE: **MetaLED** luminaires can be equipped with SurePath BLE Bluetooth addressable Gateway modules.
[See Data Sheet.](#)



MD/M3/LI/WH/ISOAU



GENERAL DETAILS

Product	LED Exit Sign
Light source	16 x white LEDs
Luminaire Lumens	N/A
Sign viewing distance	36m
Construction	Epoxy coated steel body with screen printed Polycarbonate legend panel
Geartray	Integral to base
Dimensions	385mm (L) x 185mm (W) x 71mm (H)
Cable entry	20mm knock-outs

Emergency Lighting Products Limited
Parbrook House, Gillmans Industrial Estate,
Natts Lane Billingshurst, West Sussex RH14 9EZ


Telephone: +44 (0) 1403 786601
Fax: +44 (0) 1403 786602
e-mail: sales@elp.uk.com

Safe in the knowledge
elp.uk.com

MetaLED

SPECIFICATION

	Maintained	Mains only
Light source	16 x white LEDs	
Colour temperature	4500K	
IP rating	IP20	
Ambient temperature (Ta)	0°C to 25°C	
Insulation class	Class I	
Supply voltage	230V ~ 50Hz	
Supply power	3.0W	2.4W
Charge power (typical)	1.7W	—
Battery	1 x 3.2V 1.8Ah LiFePO ₄	—
Weight	1.6kg	1.4kg



ORDER CODES

Description

MD/M3/LI/WH	Maintained emergency exit sign	
MD/M3/DA/LI/WH	Maintained DALI emergency exit sign	
MD/230/WH	Mains only exit sign	
MD/230D/WH	DALI Mains only exit sign	
OPTIONS:	/BLE	Wireless DALI emergency
LEGENDS:	/ECAR	EC Format – Arrow Right
	/ECAL	EC Format – Arrow Left
	/ECAD	EC Format – Arrow Down
	/ISOAR	ISO Format – Arrow Right
	/ISOAL	ISO Format – Arrow Left
	/ISOAU	ISO Format – Arrow Up
	/ISOAD	ISO Format – Arrow Down

Emergency Lighting Products Limited
Parbrook House, Gillmans Industrial Estate,
Natts Lane Billingshurst, West Sussex RH14 9EZ

Telephone: +44 (0) 1403 786601
Fax: +44 (0) 1403 786602
e-mail: sales@elp.uk.com

Safe in the knowledge
elp.uk.com